



 ageCheckPoint
 224
 1586 - 6

 byte S2A SanceLed0350752A
 8304-5439
 8304-5439

 byte S2A SanceLed0350752A
 127651 0.1
 127651 0.1

 byte S2A SanceLed0350752A
 127651 0.1
 127651 0.1

 byte S2A SanceLed0350752A
 127651 0.1
 127651 0.1

 byte S2A SanceLed03507525 1.51
 127651 0.1
 12804 FB

 byte S2A SanceSanceLed0350752 1.51
 12804 FB
 12804 FB

 byte S2A SanceSanceLed0350752 1.51
 12804 FB
 12804 FB

 byte S2A SanceSanceLed0350752 1.51
 12804 FB
 12804 FB

 byte S2A SanceSanceLed0350 FB
 12804 FB
 12804 FB

203 11
 \*\*
 Poetic2/17, A3 02
 Lis #562
 Poetic2/17, A3 02
 Lis #562
 Poetic2/19, B5 19
 \*\*
 Poetic2/19, B5 19
 \*\*
 Poetic2/19, B5 19
 Poetic2/19
 Poetic2/19
 Poetic2/19
 Poetic2/19
 Poetic2/

SESSION ID: CA1515B

# Accelerating Digital Design via the Cloud

SPEAKER(s):

NICOLAS PERRIN FOUNDER OF PERRINN 424

LIVEWORX.COM | #LIVEWORX

GOALS



Bring awareness to PERRINN 424

How you can follow and participate

How Onshape has made this possible



### PERRINN 424: Why



- Obsession for performance, speed and records
- Extensive experience at the top level of motorsport
- Commitment to advancing innovation



### PERRINN 424: The Challenge







PERRINN 424: How



### A network of talented **people** + **software** companies













### **PERRINN 424: Support and Invest**





### PERRINN.com

Chat with us

Invest in PERRINN digital shares





Creation process in the cloud

## **424 TECHNICAL SPECIFICATION**

### *"424* has to become and remain the fastest electric car in the world."

### **TECHNICAL SPECIFICATION:**

- Chassis made entirely of composite material
- Weight: 1,000kg (500kg chassis & 500kg powertrain)
- 3 Formula E motors (one front, two rear)
- Power: 750kW (250 front, 500 rear)
- Transmission: Four-Wheel-Drive, single speed
- Battery: 50 kWh, centrally mounted
- Acceleration: 0 100kph in 2.0 sec
- Top speed: 360kph
- Advanced aerodynamics (DRS)





# graphics Onshape Simulation for lightweighting and total mass CFD aerodynamics TOTALSINUK

STL real time

### **DIGITAL TWIN**



### **DIGITAL TWIN: Aerodynamic development**







Unorm 0.20 0.40 0.60 0.80 1.00

424 generates aerodynamic efficiency of

5.5:1 6.5:1 with DRS activated.

RUN092 - 40-60-180kph

diff strakes obd

24



# **DIGITAL TWIN: Real time driving simulation**









Laptime 5:07.50



What happens when we push the limits

### **DIGITAL TWIN: Aerodynamic instability**





Other use of simulation

### **DIGITAL TWIN: Engineering simulations**









### **DIGITAL TWIN: Rendering studio**







### **DESIGN IN THE CLOUD**

Rear casing stiffening brace has been designed by

4 people

Located on 3 continents





Onshape empowers our distributed team.

- Collaboration tools
- Branching and merging
- Public data sharing

### **DESIGN IN THE CLOUD**





open source

### **PERRINN 424: Support and Invest**





### PERRINN.com

Chat with us

Invest in PERRINN digital shares





Andread and a second se

RENDERE HTTP: UN EXTENSECTORENEM UN EXTENSECTORENEMENT UN EXTENSECTORENEMENT UNITED AND TORENEMENT UNITED AND TORENEMENT UNITED AND TORES

# Please fill out the session survey.

Take your post-session survey(s) either in the event mobile app or via email post-event.

Your feedback provides us with valuable information on how to shape future content strategy for the event!

# **PROVIDE SESSION FEEDBACK**



nin zuite nuit. Ne contue nema Literatur tema President tema Presi

# THANK YOU

LIVEWORX.COM | **#LIVEWORX** 

ptc.com

